



MODEL	XP-12FD
Lifting Capacity*	12,000 Lbs. / 5443 Kg.
*Max Capacity / Front Axle	6,000 lbs. / 2722 Kg.
*Max Capacity / Rear Axle	6,000 lbs. / 2722 Kg.
A - Height Overall:	144" / 3403 mm.
B - Width Overall (Outside of Base Plate):	155" / 3937 mm.
C - Width (Outside of Columns):	146" / 3708 mm.
D - Cover Height:	2" / 51 mm.
E - Inside Columns:	118" / 2997 mm.
F - Reach (Front Arm Min.):	39" / 991 mm.
G - Reach (Front Arm Max.):	59" / 1499 mm.
H - Reach (Rear Arm Min.):	39" / 991 mm.
I - Reach (Rear Arm Max.):	59" / 1499 mm.
J - Min. Pad Height:	5" / 127 mm.
K - Rise:	69" / 1753 mm.
L - Max Lift Height (Pad Only):	74" / 1880 mm.
M - Max Lift Height (6" Adapter):	80" / 2032 mm.
N - Drive-Thru Clearance:	103" / 2616 mm.
Motor (*)	220 VAC / 60 Hz. 1Ph.
Time of full Rise:	55 Seconds
Max Load Per Arm:	3,000Lbs. / 1361 Kg.

* Special Voltages Available Upon Request.

The design, material and specifications are subject to change without notice.