



MODEL	HD-7PX	HD-7PXW
Style	Super Tall / Narrow	Super Tall / Wide
Lifting Capacity*	7,000 Lbs. / 3175 Kg.	7,000 Lbs. / 3175 Kg.
*Max Capacity / Front Axle	3,500 Lbs. / 1588 Kg.	3,500 Lbs. / 1588 Kg.
*Max Capacity / Rear Axle	3,500 Lbs. / 1588 Kg.	3,500 Lbs. / 1588 Kg.
A - Overall Width	99-3/4" / 2534 mm.	116-3/4" / 2985 mm.
B - Outside Length	198" / 5029 mm.	198" / 5029 mm.
C - Overall Length	224" / 5690 mm.	224" / 5690 mm.
D - Height of Columns	158" / 4011 mm.	158" / 4011 mm.
E - Min. Runway Height	4-1/2" / 114 mm.	4-1/2" / 114 mm.
F - Max. Rise	140" / 3556 mm.	140" / 3556 mm.
G - Max. Lifting Height	145" / 3685 mm.	145" / 3685 mm.
H - Width Between Posts	89-3/4" / 2280 mm.	106-3/4" / 2711 mm.
I - Runway Width	19" / 483 mm.	19" / 483 mm.
J - Width Between Runways	37-1/4" / 946 mm.	37-1/4" - 44" / 946 mm. - 1118 mm.
K - Length of Runways	188" / 4775 mm.	188" / 4775 mm.
Min. Wheelbase @ Rated Capacity	135" / 3429 mm.	135" / 3429 mm.
Min. Wheelbase @ 75% Capacity	115" / 2921 mm.	115" / 2921 mm.
Min. Wheelbase @ 50% Capacity	95" / 2413 mm.	95" / 2413 mm.
Min. Wheelbase @ 25% Capacity	80" / 2032 mm.	80" / 2032 mm.
Locking Positions	30	30
Lock Spacing	Every 4" / 102 mm.	Every 4" / 102 mm.
Lifting Time	35 Seconds	45 Seconds
Standard Motor (*)	220 VAC / 60 Hz. 1Ph.	220 VAC / 60 Hz. 1Ph.