## RIM CLAMP TIRE CHANGERS

TC-530 Semi-automatic Rim clamp tire changer

· Swing arm style

Features:

- Manual operation of mount/demount tool
- Four pneumatic clamps and double acting cylinders
- Side mounted bead breaker
- Bead seating inflation jets are integrated in the clamping jaws insuring quick and safe inflation
- Includes water separator, lubricator and air pressure regulator

Bead breaker





Semi-automatic Heavy duty Rim clamp tire changer



## Features:


- · Swing arm design
- Handles tires to 47" diameter and rim widths to 15"
- Bead seating inflation jets are integrated in the clamping jaws insuring quick and safe inflation
- Twin clamping cylinders provide more power to hold the most difficult rims
- Conveniently located and powerful bead breaker
- No scratching. Machine never contacts rim eliminating accidental damage
- Large diameter hex mount / demount shaft for extra rigidity
- Pressure limiter, water separator and oiler are standard

This model has power to spare and a 26" x 26" square turntable that can handle wheel diameters up to 47" with ease.

SPECIFICATIONS: TC-530 TC-950 Max wheel diameter 38" 47" 3"-12" 3"-15" Max wheel width Rim diameter inside 12"-23" 15"-28" Rim diameter outside 10"-20" 13"-24" Working pressure 8-10 bar 8-10 bar 1 ½ HP 110 vac Power supply 110 vac

2500 kg

2500 kg







Quickly attaches over clamps to accommodate motorcycle wheels.