WHEEL BALANCERS

We offer the best value in the industry on these wheel balancers—



Features:

- Self-calibrating
- Weight storage
- Pegs for accessories
- 8" long shaft with 35mm diameter
- Three auto STD centering cones
- ST,AL1 AL2,AL3, AL4 balancing methods
- Speed nut comes standard



Optional: Light truck cone set –

Specifications	WB-1030	WB-953
Cycle time	10 sec.	10 sec.
Method of data entry	keypad	keypad
Tire diameter	35″	39"
Tire width	1 ½" - 20"	1 ½"- 20″
Rim diameter	10"-24"	10"-24"
Wheel weight	143 lbs.	150 lbs.
Accuracy	1 gram	1 gram
Power requirements	110 vac	110 vac

Features:

- Self calibrating
- Self diagnosis
- Optimization program
- Static balancing
- alu-s balancing for light alloy rims
- Split function (hidden weights)
- Multiple operator program
- Three centering cones
- Weight storage
- Pegs for accessories
- Hood, hammer, speed nut and caliper standard
- Optional motorcyle adapter is available

-11:::00%

Optional: motorcycle adapter kits –

These are top performing balancers at an affordable price. They have all the features of the big guys. Standard features include: self-calibrating, dynamic, static and alloy capability, and a speed nut. The quick keypad data entry system makes tire balancing fast and efficient.